LGAI Technological Center, S.A. Campus UAB - Ronda de la Font del Carme s/n 08193 Bellaterra (Barcelona) - Spain T +34 93 567 20 00 F+34 93 567 20 01 www.applus.com





CERTIFICATE



No.

0370-CPR-0349

CERTIFICATE OF CONSTANCY OF PERFORMANCE

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

SMOKE AND HEAT CONTROL SYSTEMS. PART 3: SPECIFICATION FOR POWERED SMOKE AND HEAT CONTROL

VENTILATORS (FANS)

PRODUCT RANGE: THGT F200₁₂₀

Produced by:

SOLER Y PALAU SISTEMAS DE VENTILACIÓN, S.L.U.

08150 PARETS DEL VALLÈS (BARCELONA)

And produced in the manufacturing plant:

17/32301811 (EUROPE) & 17/32301816 (EUROPE)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 12101-3:2015

under system 1 are applied and that the product fulfils all the prescribed requirements set out above.

This certificate was first issued on 28th September 2005 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly. It is confirmed and modified on 2nd February 2018.

The monitoring assessment will be done before November 2018

Bellaterra, 2nd February 2018

Jordi Brufau Redondo

General Manager

Tèchnological Center, S.A.

LGAI Technological Center, S.A.

Xavier Ruiz Peña

Product Conformity B.U., Managing Director

This document is not valid without its technical annex, whose number coincides with the number of certificate.



LGAI

LGAI Technological Center, S.A. (APPLUS)
Campus UAB s/n — Ronda de la Font del Carme, s/n
E - 08193 Bellaterra (Barcelona)
T +34 93 567 20 00
F +34 93 567 20 01
www.appluslaboratories.com



Technical Annex Ed.3 02/02/2018

TECHNICAL ANNEX 0370-CPR-0349

CERTIFICATE OF CONSTANCY OF PERFORMANCE

1.- Application:

- Extractor tested inside the furnace.
- Extractor F200 (120).
- Dual use.
- · Inlet and outlet air flow in horizontal direction

2.- Characteristics:

- Motor: WEG / ABB (80 to 315)
- Rated frequency: 50 /60 Hz
- Rated Voltage motor: 400 V.

3.- Accessories:

- Back draft shutter clar (CLAR) with references "CLAR-560" and "CLAR-1250" placed after the motor and impeller
- Outlet guard protection (DEF. DES. TGT/THGT).
- Inlet guard protection (DEF. ASP. TGT/THGT)
- Kit box
- Matching flange (ARO BRIDA TGT/THGT) with reference "ARO BRIDA TGT/THGT-12540 N"
- Flexible connection (ACOPEL F400 N) with reference "ACOPEL F400-1250/200N"
- Support feet (PIE SOP. TGT/THGT)
- Antivibration mount (AM-ANTIVIBRATION MOUNTS [AVM])
- Isolators FProtect from Gave
- Variable frequency driver with reference "CFW09 0060 T3848 SSZ"
- Terminal box/block WEG
- Circular sound attenuator (SIL-CZ/SIL-CZO) with reference "SIL-CZ"

The complete technical data of the certified range **THGT F200 (120)** are detailed in the technical file and the range report no 17/13774-2142.

Essential characteristics	Clauses in this European Standard	Mandated level(s) or class(es)
Response delay - Opening under wind load within a given time; - Opening under snow load within a given time.	4.1.1	NPD
		NA
Operational reliability - Application categories; - Motor rating.	4.2.2	 Thermally uninsulated Installation inside and outside smoke reservoir. Horizontal direction of motor shaft Direct feed or by converter Dual purpose use
	4.2.3	NPD
Effectiveness of smoke/hot gas extraction: - Gas flow and pressure maintenance during smoke and heat extraction test.	4.3.2	+/-20% (P _s)
Resistance to fire	4.4	F400(120)
Ability to open under environmental conditions - Opening under wind load within a given time; - Opening under snow load within a given time.	4.5	NPD
		NA
Durability of operational reliability	4.6	NPD

